

Art. 305

POCKET PULSE

Inverter Single-Phase Synergic Pulse MIG/
MAG Welding Machine.

- Single Pulse
- Gas & Gasless Operation
- 5Kg Spool Holder



SPECIFICATIONS

Single Phase Input	240 V +15% / -20% 50/60 Hz
Fuse rating (slow blow)	16 A
Input power	5,5 kVA 20% 3,7 kVA 60% 2,7 kVA 100%
Min.-max. Welding Current	20 ÷ 185 A
Duty Cycle (10 min 40°C) According to IEC 60974-1	185 A 20% 140 A 60% 110 A 100%
Stepless Regulation	Electronic
Standard Supplied Synergic Programs	0,6/0,8/0,9/1,0 Fe 0,9 Cored 0,8/0,9 Inox 0,9/1,0 Al 0,8/0,9 CuSi3%
Maximum Wire Spool Size	Ø 200 mm/5 kg
Protection class	IP 23 S
Weight	13.5 kg
Dimensions (WxLxH)	196 x 458 x 380 mm

PRODUCT & ACCESSORIES

Art.	Description
305	Cebora 1820/M Synergic Pocket Pulse MIG
3-080-916	CEBORA Drive Roll 0.8 U - 1.0 U
243	MB24 Style Mig Torch 3m
UL-G0912	Univeral Graphite liner kit 0.9mm-1.2mm
M5-356102	5356 x 1.0mm 2Kg Spool
IO-1451	Argon regulator

Please note: Power source, torch, regulator sold separately

The power source can be powered by motor generators
(Min. 6 kVA)