

Art. 326

PLASMA SOUND PC 50/M

Inverter Plasma Cutter

- 240V Single Phase
- Max Cut: 20mm
- Severance Cut: 25mm
- Complete with:
CP70 6m Plasma Torch
Earth Lead 4m and Clamp
Industrial Air Filter Regulator



SPECIFICATIONS

Single Phase Input	240 V $\pm$ 10% 50/60 Hz
Fuse rating (slow blow)	32 A
Input power	7,8 kVA 40% 5,8 kVA 60% 5,3 kVA 100%
Current adjustment range	20 $\div$ 50 A
Duty Cycle (10 min 40°C) According to IEC 60974-1	50 A 40% 42 A 60% 33 A 100%
Thickness on steel: Recommended - Max - (Severance)	15 mm 20 mm (25) mm
Torch length	6 m
Air consumption	210 l/min @ 5.5 bar
Stepless regulation	Electronic
Protection class	IP 23 S
Weight	23 kg
Dimensions (WxLxH)	286 x 590 x 406 mm

PRODUCT & ACCESSORIES

Art.	Description
326	Cebora Plasma Sound PC50/M 240V <i>Includes torch, earth lead & clamp, regulator</i>
CP70-1626	Cebora CP70 6m Plasma Torch
CP70-1626.15	Cebora CP70 15m Plasma Torch
CP70-1627	Cebora CP70 6m Plasma Profile Torch
CP70-1627.15	Cebora CP70 15m Plasma Profile Torch
441	Cebora Analog interface
1656	CEBORA Trolley

The power source can be powered by motor generators