

Art. 336

PLASMA SOUND PC 110/T

Inverter Plasma Cutter. “On Air” Ignition.

- 415V Three Phase
- Max Cut: 40mm
- Severance Cut: 50mm
- Complete with:
 - 162C MAR Hand Torch 6m
 - Earth Lead 4m and Clamp
 - Industrial Air Filter Regulator



SPECIFICATIONS

Three Phase Input	415 V $\pm$ 10% 50/60 Hz
Fuse rating (slow blow)	25 A
Input power	20,5 kVA 50% 16,5 kVA 60% 15,5 kVA 100%
Current adjustment range	20 ÷ 110 A
Duty Cycle (10 min 40°C) According to IEC 60974-1	110 A 50% 95 A 60% 90 A 100%
Thickness on steel: Recommended - Max - (Severance)	35 mm 40 mm (50) mm
Torch length	6 m / 15 m
Air consumption	250 l/min @ 5.5 bar
Stepless regulation	Electronic
Protection class	IP 23 S
Weight	34 kg
Dimensions (WxLxH)	297 x 504 x 558 mm

PRODUCT & ACCESSORIES

Art.	Description
336	Cebora Plasma Sound PC110/T 415V <i>Includes torch, earth lead & clamp, regulator</i>
CP162-1631	Cebora 162C MAR Hand Torch 6m
CP162-1631.15	Cebora 162C MAR Hand Torch 15m
CP162-1632	Cebora 162C DAR Machine Torch 6m
CP162-1632.15	Cebora CP162C DAR Machine Torch 15m
441	Cebora Analog interface
1670	CEBORA Trolley wheel kit

The power source can be powered by motor generators