

Art. 337

PLASMA SOUND PC 130/T

Inverter Plasma Cutter. “On Air” Ignition.

- 415V Three Phase
- Max Cut: 50mm
- Severance Cut: 60mm
- Complete with:
162C MAR Hand Torch 6m
Earth Lead 4m and Clamp
Industrial Air Filter Regulator



SPECIFICATIONS

Three Phase Input	415 V \pm 10% 50/60 Hz
Fuse rating (slow blow)	32 A
Input power	22 kVA 80% 21 kVA 100%
Current adjustment range	20 ÷ 130 A
Duty Cycle (10 min 40°C) According to IEC 60974-1	130 A 80% 125 A 100%
Thickness on steel: Recommended - Max - (Severance)	40 mm 50 mm (60) mm
Torch length	6 m / 15 m
Air consumption	250 l/min @ 5.5 bar
Stepless regulation	Electronic
Protection class	IP 23 S
Weight	40 kg
Dimensions (WxLxH)	297 x 613 x 558 mm

PRODUCT & ACCESSORIES

Art.	Description
337	Cebora Plasma Sound PC 130/T (415V) <i>Includes torch, earth lead & clamp, regulator</i>
CP162-1631	Cebora 162C MAR Hand Torch 6m
CP162-1631.15	Cebora 162C MAR Hand Torch 15m
CP162-1632	Cebora 162C DAR Machine Torch 6m
CP162-1632.15	Cebora CP162C DAR Machine Torch 15m
433	Cebora Plasma Interface
1671	CEBORA Trolley wheel kit for Art.337

The power source can be powered by motor generators